

# **#UP1026**Jeans miniskirt

Take your fashion game up a notch with this jeans miniskirt! It features the classic 5-pocket style, an uneven hem, a waistband with belt loops, and an alluring fitted cut. Although this is an advanced sewing project, the result is totally worth the effort as it has a timeless style that will last for years.



#### Material

- 110 x 150 cm of denim fabric
- 25 x 110 cm of light poplin or broadcloth
- 110 x 90 cm of fusible interfacing
- All-purpose thread
- Jeans needle (size 16-18)
- 1x zipper for pants (length 15 cm)
- 1x button (1.5 cm wide)
- OPTIONAL: topstitch thread
- OPTIONAL: 4x rivets (1 cm wide)



#### Print & Assemble

- First, be sure to use ACROBAT READER to open your PDF sewing patterns. It's free!
- Then, open your file and click on the LAYERS icon (left side of the screen) and uncheck all the sizes you won't need.
- Now, click on the PRINT icon at the top of the screen. The print settings will appear, so verify that the ACTUAL SIZE option is checked. Click on the PRINT button!

• A 5 x 5 cm (and 2 x 2") control square is provided to ensure that your pattern is true to size.

Back

• To ASSEMBLE, cut the sheets at the bottom and right margins, as indicated. Each sheet is labelled with a letter and a number (AI, B2...), so tape them together in numerical and alphabetical order. The sheets on one row should have the same letter, and the ones on the same column should have the same number.

# Sizing Guide

	XXS	XS	S	M	L	XL	XXL
Bust	85 cm	89 cm	93 cm	99 cm	105 cm	113 cm	121 cm
Waist	64 cm	68 cm	72 cm	78 cm	84 cm	92 cm	100 cm
Hips	92 cm	96 cm	100 cm	106 cm	112 cm	120 cm	128 cm

This pattern is drafted according to a standard height of **1.64 m**.

#### **Garment measurements**

Length: 34.5 cm



# **#UP1026**

# Jeans miniskirt

#### **Pattern Pieces**

- Coin pocket, lx fabric
- Pocket backing, 2x fabric
- Pocket lining, 2x lining
- Front, 2x fabric
- Fly shield, 1x fabric 1x interfacing
- Fly facing, lx fabric lx interfacing
- Back pocket, 2x fabric
- Back, 2x fabric
- Back yoke, 2x fabric
- Belt loop, 2x fabric
- Belt, lx fabric lx interfacing

# Sewing Assembly

Unless otherwise specified, sew using a **1 cm** wide seam allowance.

- 1. Fuse the belt, fly shield, and fly facing.
- 2. Hem the top of the coin pocket (turn twice 1 cm) and sew it on the pocket backing, on the right-hand side of the garment.
- 3. Assemble the front pockets.
- 4. Sew the center front, leaving an opening above the notch.
- 5. Assemble the front fly and topstitch the center front.
- 6. Hem the top edge of the back pockets (turn twice 1 cm) and sew them to the back panels.
- 7. Sew the yokes to the back panels. Topstitch above the seams.
- 8. Sew the center back and topstitch it.
- 9. Sew the side seams, leaving an opening below the lower notches.
- 10. Sew the side slits.
- 11. Make the belt loop and cut the pieces to get six belt loops. Sew them on the top of the garment (see pattern for placement markings).
- 12. Sew the belt on the top of the garment.
- 13. Sew the belt loops to the top of the belt.
- 14. OPTIONAL: add a row of stitching roughly 1 cm above the raw hems to prevent them from fraying when washing.
- 15. Add the button and buttonhole (see pattern for placement).
- 16. OPTIONAL: install rivets on the front pocket openings.



Share a photo of you wearing proudly your new jeans skirt with

### #unfetteredpatterns!





























